Technical Information

Foamaster® NO 2309

(old : Foamaster® 309-A)



Foamaster® NO 2309 is formulated from proven defoamer components general

for use in a variety of water-based paints. Foamaster® NO 2309 provides efficients defoaming and excellent compatibility with aqueous

paint systems.

Complex mixture of petroleum oil, hydrophobic silica, fatty derivatives chemical nature

Properties

physical form Pale amber, opaque liquid

shelf life When stored under the usual appropriate storage conditions, the

product can be stored for 1 year.

typical properties

(no supply specification)

Pale amber, opaque appearance density at 25°C 0.85 - 0.89 g/cm3viscosity at 25°C (Brookfield) 100-700 mPa·s

Application

In paints formulations, Foamaster® NO 2309 is best added in two stages, one addition at the grind stage and a second, usually smaller, addition during let-down.

Foamaster® NO 2309 contributes to excellent paint application, does

not cause fish-eyes, nor effect the final paint film.

recommended concentrations

The quantity of Foamaster® NO 2309 required will depend upon the system under consideration, but as a rule, a total addition should not

exceed 0.5% on total paint weight.

Foamaster®	ΝО	2300
roamastei	INO	2309

Safety
When handling these products, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

 $^{\text{\tiny{\$}}}$ = registered trademark, $^{\text{\tiny{TM}}}$ = trademark of BASF Group, unless otherwise noted

BASF SE Formulation Additives 67056 Ludwigshafen, Germany www.dispersions-pigments.basf.com formulation-additives-europe@basf.com formulation-additives-asia@basf.com formulation-additives-nafta@basf.com formulation-additives-southamerica@basf.com