

Foamaster® WO 2350

(old: Dehydran® P 3215)



general	antifoam/defoamer for latex
chemical nature	formulation based on white oil and alkyl polyalcoxyether

Properties

physical form	opaque whitish liquid				
shelf life	When stored under the usual appropriate storage conditions, the product can be stored for 1 year.				
typical properties (no supply specification)	<table><tr><td>density at 20 °C (68 °F)</td><td>~ 0.9 g/cm³</td></tr><tr><td>Brookfield viscosity at 23°C (73°F)</td><td>~ 700 mPa.s</td></tr></table>	density at 20 °C (68 °F)	~ 0.9 g/cm ³	Brookfield viscosity at 23°C (73°F)	~ 700 mPa.s
density at 20 °C (68 °F)	~ 0.9 g/cm ³				
Brookfield viscosity at 23°C (73°F)	~ 700 mPa.s				

Application

Foamaster® WO 2350 is a defoamer for latex polymerization, specifically used in monomer “stripping”.

recommended concentrations	The dosage is generally 0.01 – 0.20% on latex. When used as a defoamer for monomer “stripping”, we recommend to prepare an aqueous dilution (2 – 10% in water).
-----------------------------------	---

Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = registered trademark, ™ = trademark of BASF Group, unless otherwise noted

BASF SE
Formulation Additives
67056 Ludwigshafen, Germany
www.basf.com/resins
service-edc@basf.com