Technical Information

Efka® PU 4050 AN

(old : Efka® PU 4050)



general

high-molecular-weight dispersing agent

Efka® PU 4050 AN is a polymeric dispersant for stabilizing inorganic and organic pigments. This results in:

- improved gloss and DOI
- reduced flooding problems
- · higher color strength
- lower viscosity

chemical nature

modified polyurethane

Properties

physical form clear, slightly yellowish liquid

shelf life Efka[®] PU 4050 AN should be stored in a cool and dry place. When

kept in original unopened containers, it can be stored for up to 4 years

from the date of manufacture.

typical properties (no supply specification)

solvent

n-butyl acetate/methoxypropyl
acetate

density at 20 °C

active ingredients
flash point

amine value

n-butyl acetate/methoxypropyl
acetate

~1.00 g/cm³

~45 %

flash point

24 °C (75°F)

~12 mg KOH/g

color ≤ 10

Application

Efka® PU 4050 AN is used in all kinds of solvent-based coatings, including high-quality industrial coatings such as automotive topcoats (OEM and refinish), coil coatings and 2-pack polyurethane coating systems. It can also be used in pigment concentrates.

recommended concentrations

inorganic pigments	10 % of oil absorption value
organic pigments	25-50 % of BET value
carbon blacks	20 % of DBP absorption value

Efka[®] PU 4050 AN should be incorporated in the mill base before adding the pigments.

Safety

When handling this product please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

BASF SE Performance Additives 67056 Ludwigshafen, Germany www.basf.com/resins service-edc@basf.com

 $^{^{\}circledR}$ = registered trademark, $^{\intercal M}$ = trademark of BASF Group, unless otherwise noted