

Dispex® Ultra FA 4404

(old: HYDROPALAT® 3204)



general

Dispex® Ultra FA 4404 is a partially neutralized chelating agent suitable for use in the manufacture of pigment suspensions, emulsion paints, slurries, etc.

Dispex® Ultra FA 4404 combines the properties of a chelating agent and polyphosphate with those of an organic dispersant thus yielding highly concentrated, stable and low-viscosity inorganic pigment suspensions, e. g. TiO₂-slurries.

chemical nature

aqueous solution of phosphonate salt

Properties

physical form

clear, light-yellow liquid

shelf life

subject to appropriate storage under the usual storage and temperature conditions, our products are durable for at least 2 years.

typical properties (no supply specification)

density at 20 °C (68°F)	~ 1.25 g/cm ³
solid content	~ 50%
pH-value (10%)	~ 6

Application

by combining Dispex® Ultra FA 4404 with Dispex® Ultra FA 4480 stable inorganic pigment pastes can be achieved. Furthermore this combination is suitable for the dispersing of inorganic and organic pigment mixtures in conformance with the slurry preparations. Dispex® Ultra FA 4404 can reduce the pot-life in aqueous 2 pack PUR coatings.

recommended concentrations

Dispex® Ultra FA 4404 should be incorporated into the water prior to charge with pigments 0.2 - 0.5%, calculated on the pigment concentration. The optimum dosage should be determined by appropriate tests.

Safety

When handling these products, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = registered trademark, ™ = trademark of BASF Group, unless otherwise noted

BASF SE
Formulation Additives
67056 Ludwigshafen, Germany
www.dispersions-pigments.basf.com
formulation-additives-europe@basf.com
formulation-additives-asia@basf.com
formulation-additives-nafta@basf.com
formulation-additives-south-america@basf.com