

Efka[®] SL 3200

(old: Perenol[®] S Conc)



general

Additive for improving the flow and the slip of solvent-based and solventless coatings.

Efka[®] SL 3200 is a solventless polysiloxane block polymer corresponding in performance to other flow or slip agents of our Perenol[®] S range.

chemical nature

copolysiloxane

Properties

physical form

clear to slightly cloudy liquid

shelf life

Subject to appropriate storage under the usual storage and temperature conditions, our products are durable for at least 2 years.

typical properties (no supply specification)

density at 20 °C (68 °F)	~ 1.05 g/cm ³
solid content	> 95%

Application

solvent-based and solventless coatings.

recommended concentrations

The dosage lies between 0.05 and 0.25%. The exact amount should be determined by appropriate tests. The product should be added before the paint is diluted to working viscosity.

Safety

When handling these products, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = registered trademark, ™ = trademark of BASF Group, unless otherwise noted

BASF SE
Formulation Additives
67056 Ludwigshafen, Germany
www.dispersions-pigments.basf.com
formulation-additives-europe@basf.com
formulation-additives-asia@basf.com
formulation-additives-nafta@basf.com
formulation-additives-south-america@basf.com